

# OI-6750 Sensor Assembly

## 2- Wire Electrochemical Toxic Gas Detector

The Otis Instruments OI-6750 Series Toxic Gas Detector is a versatile assembly that uses an electrochemical sensor to detect a variety of gases. 2-Wire Loop-Powered to withstand extreme climatic conditions and harsh environments. Magnetic switches allow for non-intrusive calibrations while in the field as well as full system settings and diagnostics.



Gas Type	Range	T <sub>90</sub>	Warranty
EC-AsH3	0-5 ppm	< 30 sec.	10 months
EC-CH2O	0-10ppm	< 30 sec.	12 months
EC-CH3SH	0-10 ppm	< 100 sec.	12 months
EC-CL2	0-10 ppm	< 60 sec.	12 months
EC-CLO2	0-5 ppm	< 120 sec.	12 months
EC-CO	0-1000 ppm	< 30 sec.	24 months
EC-ETO	0-10 ppm	< 80 sec.	12 months
EC-F2	0-1 ppm	< 80 sec.	12 months
EC-H2	0-4%	< 60 sec.	18 months
EC-H2S	0-100 ppm	< 30 sec.	24 months
EC-H2S2K	0-2000 ppm	< 25 sec.	24 months
EC-HBr	0-30 ppm	< 40 sec.	12 months
EC-HCL	0-200 ppm	< 300 sec.	12 months
EC-HCN	0-50 ppm	< 70 sec.	12 months
EC-HF	0-10 ppm	< 90 sec.	12 months
EC-NH3	0-100 ppm	< 90 sec.	12 months
EC-NH3300	0-300 ppm	< 120 sec.	12 months
EC-NH3A	0-1000 ppm	< 120 sec.	12 months
EC-NO	0-250 ppm	< 40 sec.	12 months
EC-NO2	0-20 ppm	< 25 sec.	12 months
EC-O2	0-25% vol.	< 15 sec.	24 months
EC-O3	0-5 ppm	< 60 sec.	12 months
EC-O3H	0-100 ppm	< 60 sec.	12 months
EC-PH3	0-5 ppm	< 30 sec.	12 months
EC-SO2	0-20 ppm	< 35 sec.	24 months

Corporate Office  
301 S. Texas Avenue  
Bryan, Texas 77803  
P: 979-776-7700

sales@otisinstruments.com  
www.otisinstruments.com

Midland Office  
3308 Norden Drive  
Midland, Texas 79706  
P: 432-563-5858

#### OI-6750 Product Specifications

Sensor Type	Electrochemical
Power Type	Loop-Powered (2-Wire)
Operating Voltage	12V to 35V DC
Current Draw	35 mA Maximum
Display Screen	102x64 Resolution Graphical LCD Screen
Product Compatibility	Gen II WireFree Transmitter (OI-5900) Gen II Wired Monitors (OI-7010, OI-7032, OI-7420, OI-7440, OI-7480)
Interface	3 Push-Buttons (MENU, ADD and SUB) 3 Magnetic, Non-Intrusive Switches for Calibration
T <sub>amb</sub> Temperature Range	-40°C to +60°C (Varies with Sensor Type)
Wired (Analog) Output	4-20 mA (2-Wire)
Product Dimensions	5.42 in. L x 6.03 in. W x 17.03 in. H (Max. Dimensions with Attachments)
Enclosure Materials	Aluminum Device Enclosure 303 Stainless-Steel Sensor Housing
Total Weight	5.75 lbs.
Product Mounting	Wall Mount (Included)
Approvals	QPS Component Certified Explosion-Proof
Hazardous Location Certification Approvals	Class I, Division 1, Groups B, C and D T <sub>amb</sub> = -40° C to +60° C
Hardware Warranty	1-Year Limited
Sensor Element Warranty	1-Year (Varies with Gas Type)
Part Number Formula	OI-6750-[Gas]-X-O OI-6750-X-X-O