

OI-9100-X WireFree Viewer

The Otis Instruments OI-9100 Series WireFree ViewTM is a hand-held, on-the-go monitoring device designed to provide realtime status updates for any GEN II WireFree gas detector, transmitter, or repeater within wireless range. Featuring a compact and user-friendly design, the OI-9100 offers convenient and efficient site monitoring, allowing users to quickly assess safety conditions while on the move.

<u>Key Features:</u>

- Real-Time Monitoring: Displays live data from GEN II WireFree devices, enabling immediate insight into site safety conditions.
- Comprehensive Data Display: The 4-line scrollable display provides essential information, including:
 - * Radio address
 - * Gas level readings
 - * RF signal strength
 - * Time since the last message
 - * Sensor type
 - * Gas type
 - * Remaining battery voltage
- Remote Device Management: Allows users to remotely review the status of multiple gas detectors onsite, enhancing safety monitoring and operational efficiency.
- Portable and User-Friendly: The hand-held form factor ensures easy transport, making it ideal for technicians, safety personnel, and maintenance teams.

<u>Ideal For:</u>

- Industrial safety monitoring
- Environmental assessments
- Onsite safety audits
- Field operations in gas detection environments


The Otis Instruments OI-9100 Series WireFree ViewTM delivers enhanced

situational awareness, providing critical gas detection data wherever needed. With its robust design and easy-to-read display, this device is an essential tool for safety professionals and site managers.

Corporate Office

301 S. Texas Avenue Bryan, Texas 77803 P: 979-776-7700 sales@otisinstruments.com

www.otisinstruments.com



3308 Norden Drive Midland, Texas 79706 P: 432-563-5858



On-The-Go Monitoring Device

Product Specifications	
Product Type	Signal-Strength Meter
Power Type	Battery-Powered
Operating Voltage	(3.7 V) Lithium Ion Rechargeable Batteries
Battery Life	Up to 16 Hours Continuous Use Battery Life per Charge
Display Screen	4x20 Character LCD Screen
Interface	Push-Button Knob
Customizable Setting Alarm Indicator	Option to Disable Red Alarm LED
T _{amb} Temperature Range	0°C to +50°C (32°F to +122°F)
WireFree (Digital) Input	Up to 255 GEN II WireFree Gas Detectors
Product Compatibility	GEN II WireFree Sensors (OI-6000, OI-6900, OI-6940) GEN II WireFree Transmitters (OI-5900, OI-5950)
WireFree Radio Options	GEN II 900 MHz Radio
Network Selectors	52 Networks (GEN II 900 MHz Radio) 78 Networks (GEN II 2.4 GHz Radio)
Enclosure Material	Aluminum Device Enclosure
Product Dimensions	4.875 in. L x 4 in. W x 1.188 in. H
Total Weight	1.15 lbs.
Hardware Warranty	1-Year, Limited
Part Number Formula	OI-9100-[Radio]



